

# DS-PD2-T12P-WEL

## Wireless Outdoor Dual-Tech Detector

DS-PD2-T12P-WEL delivers long range signaling, multi-award-winning two-way wireless technology, heightened false alarm immunity with Dual-Vision Pet Immune detection technology, as well as a host of features that make this a steadfast detector that's quick and easy to install. Offering 90° detection (install between 1~1.5m), the brand-new DS-PD2-T12P-WEL can provide a maximum detection range of 12m.



### AVAILABLE MODEL

DS-PD2-T12P-WEL	Wireless Outdoor Dual-Tech Detector
DS-PDB-EX-Wall bracket	Wall bracket (Need to order separately )
DS-PDB-EX-Adapter	Detector Bracket for Extending coverage angle to 90 degrees (Need to order separately, using together with DS-PDB-EX-Wall bracket)
DS-PDB-EX-Fixed bracket	Fix two external detectors to give added coverage to perimeters (Need to order separately)

\*All bracket need to order separately.

## MAIN FEATURES

- Microwave + 2 independent PIR
- Detection Range : 12m with Volumetric coverage 90°
- Alarm: Tamper Alarm, Intruder Alarm
- Adjustable PIR/MW range
- Dual-Vision Pet Immunity (up to 24kg)
- Anti-Sway Analytics
- Blue Wave Technology
- IP55 Heavy Duty Design

## SPECIFICATION

Wireless Outdoor Dual-Tech Detector	
<b>Detection Range</b>	12m, detection angle: 90°
<b>Detection Speed</b>	0.25m/s ~ 3m/s
<b>Animal Immunity</b>	Up to 24kg
<b>Power Supply</b>	2 × 3V 4700mAH Lithium Battery packs, up to 3 years Battery life
<b>Operation Temperature</b>	-25°C ~ +60°C
<b>Dimension(L*W*H)</b>	188mm*77mm*84mm
<b>Weight</b>	300g (without bracket)
<b>Installation Environment</b>	Outdoor
<b>Installation Height</b>	1-1.5m
<b>Transmission Frequency</b>	433MHz
<b>Transmission Range</b>	800m(in open space)

