



CYB TS

CYB TS Motorized Tripod Turnstile

CYB TS Motorized Tripod Turnstile
(w/ controller and RFID reader)

CYB TS Motorized Tripod Turnstile
(w/ controller and fingerprint & RFID reader)

CYB TS tripod turnstile series is a motorized tripod turnstile series designed for high-traffic volume.

CYB TS is an automatic tripod turnstile series designed for smooth and silent operation and consumes very little power. It is made of stainless steel that offers high durability. CYB TS is also surprisingly compact and designed to operate in small workspace.

CYB TS tripod arms are normally held in a locked position, thus denying access to the secured side. Upon the reader (RFID and/or fingerprint) in CYB TS positively recognizing a user's valid access card or fingerprint, arms unlock and automatically rotate at a slight push.

During emergencies and power outages the tripod arms completely collapse, thereby ensuring users FAST unencumbered exit to safety. When the power is on, the arm will automatically lift up to form a secure lane. CYB TS provides both security and convenient space, all in a very durable compact design.

Features

Reliability

stainless steel casework & tripod arms ensure long-lasting.

Safety Features

- Tripod-arms unlock & drop during emergencies / power loss.
- All smooth finishing.
- Visual indicator for granted access (or denied).
- Ergonomic design makes card and fingerprint authentication fast & simple for users.
- Secure. Supports Anti-tailgating.

Built-in Reader Integration

- **CYB TS** series ships already integrated with our customers' preference for either card or fingerprint access control reader. This greatly reduces installation time & expense.
- **CYB TS** series and associated access control readers are all factory-tested prior to shipping.
- **CYB** provides true plug'n play turnstiles with the lowest possible total cost of ownership in the industry.

Specifications

Power Requirements		AC100 ~ 120V/200 ~ 240V, 50/60Hz
Power Consumption	Star ting	73W
	Standby	20W
	Unlock	63W
Working Temperature		-28°C to 60°C
Working Humidity		5% to 80%
Working Environment		Indoor / Outdoor (if sheltered)
Max. Speed of Throughput	RFID	30 people per minute
	Fingerprint	25 people per minute
		465
Lane Width (mm)		1200 * 300 * 1010 (mm)
Dimension (L*W*H)		1310 * 420 * 1100 (mm)
Packing Dimensions (L*W*H)		66kg
Net Weight (kg)		90kg
Weight with Packing (kg)		SUS304 Stainless Steel
Cabinet Material		Acr ylic
Lid Material		SUS304 Stainless Steel
Barrier Material		Rotating
Barrier Movement		Suppor ts
Emergency Mode		Medium
Security Level		2 million
MCBF		
Options/Accessories		Counter, Card Receiver Box, SUS316 Cabinet and Lid, Remote Control
Warranty		1 year

Dimensions (mm)

