

## CYB Pro Serisi 11



Face recognition terminal is a kind of access control device. It can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

7-inch LCD touch screen, 2 Mega pixel wide-angle lens

Recognition distance: 0.3 to 3 m

Face recognition duration  $< 0.2$  s/User

Face recognition accuracy rate  $\geq 99\%$

Supports M1 card

Face mask detection

6000 face capacity, 50,000 card capacity, and 150,000 event capacity

Supports ISAPI, ISUP 5.0, TCP/IP (IPv4 and IPv6)

QR code recognition

Connects with secure door control unit to realize 2 doors control. Using key fobs to control the 2 doors is available

Supports single person and multiple people (up to 5 people) recognition

## Specification

<b>System</b>	
Operation system	Linux
<b>Display</b>	
Resolution	600 × 1024
Size	7-inch
Type	Touch screen
<b>Video</b>	
FOV	HFOV= 88°; VFOV= 44°
Pixel	2 MP
Lens	Dual-lens
WDR	Support
Video standard	PAL (Default)/NTSC
<b>Network</b>	
Wired network	Support 10/100/1000 Mbps self-adaptive
<b>Interface</b>	
Alarm input	
Alarm output	2 1 1 Type-A (For
USB	Module)
Network interface	1
RS-485	1
Wiegand	1
Lock output	1 1 1
Exit button	1
Door contact input	
TAMPER	
<b>Capacity</b>	
User capacity	
Card capacity	6000
Face capacity	50,000
Event capacity	6000
<b>Authentication</b>	150,000
Face recognition accuracy rate	
Card type	
Card reading distance	≥ 99%
Card reading duration	M1 card
	0 to 5 cm
Face recognition duration	< 1 s
Face recognition distance	< 0.2 s per person
<b>General</b>	
Power supply	0.3 to 3 m
<b>Working temperature</b>	
Working humidity	12 VDC/2 A
Power consumption	-30 °C to 60 °C (-22 °F to 140 °F)
Protective level	10 to 90% (no condensing)
	≤ 10 W
	IP65

Dimensions	110.5 mm × 209.2 mm × 24 mm (4.35" × 8.24" × 0.94")
Weight	Gross Weight: 1.06 kg (2.34 lb) Net Weight: 0.57 kg (1.26 lb)
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Japanese, Korean
<b>Function</b>	
Configuration via Web browser	Support
Hik-Connect	Support
Two-way audio	Support
QR code recognition	Support
Face mask recognition	Support
Time synchronization	Support
Face recognition	Support
Face anti-spoofing	Support
Live view	Support
Audio prompt	Support

## Dimension

