

## CYB Ekonomi Serisi 2



Barrier open/closed, free accessing, forbidden mode are selectable.

LED indicates the entrance/exit and passing status.

Fire alarm passing: when the fire alarm is triggered, the barrier will be dropped automatically for emergency evacuation.

Easy integration of any 3rd access control system via relay output.

## Specification

<b>System</b>	
Motor	/
MCBF	≥ 3 million times
<b>Interface</b>	
Exit button	2
Fire alarm input	1
<b>Hardware</b>	
Access controller	Not supplied
<b>Function</b>	
Audio prompt	Not support
Keypad configuration	Support
<b>General</b>	
Throughput	30 to 60 persons per minute The actual throughput is affected by the person passing rate and passing method.
Lane width	550 mm (21.65")
Barrier material	1.2 mm stainless pipe
Pedestal material	SUS304 stainless steel 1.2 mm
Power consumption	Standby: 15 W Working: 30 W Peak: 40 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	0% to 95% (No condensing)
Protective level	/
Dimensions	Without package: 502 mm × 202 mm × 1010 mm (19.8" × 8.0" × 40.0") With package: 700 mm × 430 mm × 1140 mm (27.56" × 16.93" × 44.88")
Weight	Net: 26.65 kg (58.75 lb) Gross: 32.75 kg (72.2 lb)
Approval	CE/CB/RoHS/REACH/WEEE
Power supply method	Power supply: 100 to 120 VAC~ / 200 to 240 VAC~, 50/60 Hz,
Language	Arabic, Indonesian, Japanese, Kazakh, Portuguese (Brazil), Spanish (Mexico), Spanish (Spain), Thai, Russian, English
<b>Configuration</b>	
Application environment	Indoor