

CYB 1200 Series

CYB -1200 Dual-Lane Flap Barrier Turnstile CYB -1211 Dual-Lane Flap Barrier Turnstile (w/ controller and RFID reader)

CYB -1222 Dual-Lane Flap Barrier Turnstile (w/ controller and fingerprint & RFID readers)











ergency Unlock

Anti-pinch

Highly Durable and Low Maintenance Costs

- Modularized structure design
- Exposed mounting holes for easy installation
 Mainly made of SPCC (option: SUS 216 stainless stain



PGIC Controller

- Equipped with a PGIC controller
- Access control
- General features and parameters settings on the controller's menu

LED Indicator

- Visual cues for correct walking direction
- Clear guidance with green and red illustration

Switchable Reader Panel

- Six panels available:
 - RFID only
 - RFID & Fingerprint
 - RFID & QR Code
 - RFID & Fingerprint & OR Code
 - RFID & Card Slot
 - RFID & Card Slot & QR Code
- Reducing middlemen's inventory pressure
- Reducing installation time & expenses

Installation Place for Facial Recognition A&C Terminals

- Diameter: 34mm
- Integration with Facial Recognition,
 Temperature and Mask Detection
 Terminals

Infrared Sensors

 16 pairs of infrared sensors for stronger tailgating detection







Specifications

Model	CYB 1200 Series
Power Requirements	AC100V to 120V / 200V to 240V, 50 to 60Hz
Working Power	50W; 22W (stand-by) Brushless Motor 10
Drive Unit	millions Up to 30 people per minute Retract
MCBF	<60dB
Technical Throughput Rate	16 pairs
Barrier Movement	Suppor t
Noise	-25°C to 65°C
Infrared Sensor	20% to 95% (non-condensing) Indoor /
LED Indicator	Outdoor (if sheltered) 600mm 1360 * 180 *
Working Temperature	1010 (mm) (±5mm) 1510 * 365 * 1216 (mm)
Working Humidity	75kg (±5kg)
Working Environment	100kg (±5kg)
Lane Width	SPCC (option: SUS316 stainless steel)
Dimensions (L*W*H)	Stainless steel (option: SUS316 stainless
Dimensions with Packaging (L*W*H)	steel) Acr ylic Wooden case IP34 5 years
Net Weight	
Gross Weight	
Cabinet Material	
Lid Material	
Barrier Material	
Packing Material	
Protection Level	
Warrantry	

Applications



