



Maximum 12 pairs of sensors

could be installed

## Specifications

Model	CYB-1000 Series
Power Requirements	AC100V to 120V / 200V to 240V, 50 to
Working Power	60Hz 50W; 22W (stand-by) Brushless
Drive Unit	Motor 3 millions Up to 30 people per
MCBF	minute Retract
Technical Throughput Rate	<60dB
Barrier Movement	5 pairs (option: ≤12 pairs)
Noise	Suppor t
Infrared Sensor	-25°C to 65°C
LED Indicator	20% to 95% (non-condensing)
Working Temperature	Indoor / Outdoor (if sheltered)
Working Humidity	600mm
Working Environment	1360 * 180 * 1010 (mm) (±5mm)
Lane Width	1510 * 365 * 1216 (mm)
Dimensions (L*W*H)	
Dimensions with Packaging (L*W*H)	(2 boxes)
Net Weight	130kg (±5kg)
Gross Weight	180kg (±5kg)
Cabinet Material	SUS304 stainless steel (option: SUS316 stainless steel)
Lid Material	SUS304 stainless steel
Barrier Material	Acr ylic
Packing Material	Wooden case
Protection Level	IP34
Warrantry	1 year

## Applications









Gyms

Airports



Stations



Government Buildings

Hotels

Banks

## Dimensions (mm)

