

CYB Pro Serisi 13



Face recognition terminal is a kind of access control device. It can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

7-inch LCD touch screen, 2 Mega pixel wide-angle lens

Recognition distance: 0.3 to 3 m

Face recognition duration < 0.2 s/User

Face recognition accuracy rate $\geq 99\%$

Supports M1 card

Face mask detection

6000 face capacity, 50,000 card capacity, and 150,000 event capacity

Supports ISAPI, ISUP 5.0, TCP/IP (IPv4 and IPv6)

Connects with secure door control unit to realize 2 doors control. Using key fobs to control the 2 doors is available

Supports single person and multiple people (up to 5 people) recognition

Specification

System	
Operation system	Linux
Display	
Resolution	600 × 1024
Size	7-inch
Type	Touch screen
Video	
FOV	HFOV= 88°; VFOV= 44°
Pixel	2 MP
Lens	Dual-lens
WDR	Support
Video standard	PAL (Default)/NTSC
Network	
Wi-Fi	Support, 2.4 G, 802.11b/g/n
Wired network	Support 10/100/1000 Mbps self-adaptive
Interface	
Alarm input	
Alarm output	2 1 1 Type-A (For
USB	Module) 1 1 1
Network interface	1
RS-485	1 1 1
Wiegand	
Lock output	
Exit button	
Door contact input	
TAMPER	
Capacity	
User capacity	
Card capacity	6000
Face capacity	50,000
Event capacity	6000
Authentication	150,000
Face recognition accuracy rate	
Card type	
Card reading distance	≥ 99%
Card reading duration	M1 card
	0 to 5 cm
Face recognition duration	< 1 s
Face recognition distance	< 0.2 s per person
General	0.3 to 3 m
Power supply	
Working temperature	
Working humidity	12 VDC/2 A
Power consumption	-30 °C to 60 °C (-22 °F to 140 °F)
	10 to 90% (no condensing)
	≤ 10 W

Protective level	IP65
Dimensions	110.5 mm × 209.2 mm × 24 mm (4.35" × 8.24" × 0.94")
Weight	Gross Weight: 1.06 kg (2.34 lb)
	Net Weight: 0.57 kg (1.26 lb)
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Japanese, Korean
Function	
Configuration via Web browser	Support
Hik-Connect	Support
Two-way audio	Support
QR code recognition	Support
Time synchronization	Support
Face mask recognition	Support
Face recognition	Support
Face anti-spoofing	Support
Live view	Support
Audio prompt	Support

Dimension

